


PAVILION UPHOLSTERY




Our selection of weather-resistant, outdoor performance fabrics come in a dynamic range of colors and are available across our collections.


ELIOS UPHOLSTERY




Birch 7740-51042




Caramel 7740-51035




Ladybird 7740-51036




Spring 7740-51037




Sodalite 7740-51039




Blue Jay 7740-51038



Basalt 7740-51034



Sparrow 7740-51041




Evergreen 7740-51040




Dark Night 7740-51033


LOUNGE UPHOLSTERY




White 7720FR-5701




Quartz 7720FR-50932




Zinc 7720FR-5703




Shea 7720FR-50931




Saffron 7720FR-50929




Cheyenne 7720FR-50928




Reed 7720FR-50930




Sea Spray 7720FR-50934



Abyss 7720FR-50935



Dark Alu 7720FR-5706



Purple 7720FR-5708

ELIOS AND LOUNGE, CONTINUED

	ELIOS 7740	LOUNGE 7720FR	Standards
Technical Properties			
Weight	13.3 oz/sqyd (450 g/m ²)	14.8 oz/sqyd (500 g/m ²)	EN ISO 2286-2
Width	55.1 in (140 cm)	70.9 in (180 cm)	
Composition	18% high tenacity polyester yarn 65% PVC 17% flocked yarn*	28% high tenacity polyester yarn 72% PVC	
Physical Properties			
Softness	2g	N/A	ASTM D5342-D5650
Abrasion resistance**	>600,000 double rubs - Heavy Duty	>600,000 double rubs - Heavy Duty	ASTM D4157 Wyzenbeek
Tear strength (warp/weft)	22 / 15 daN	18 / 15 daN	DIN 53363
Tensile strength (warp/weft)	160 / 100 daN/5 cm	150 / 150 daN/5 cm	ISO 1421
Light stability	GS=4 at 700h / >1,500 QUV	GS=4 at 700h / >1,500 QUV	ASTM G154: UVA340
Mold Resistance	Method A, degree 0, excellent	Method A, degree 0, excellent	ISO 846-A
Extreme working temperatures	14°F / +158°F	-22°F / +158°F	
Flame Retardancy			
Rating	Pass	Pass	IMO MSC.307(88) (2010FTP Code) Annex 1 Part 8
Management Systems			
Quality			ISO 9001
Environment			ISO 14001
Certifications, Labels, Warranty, Recycling			



5 year
warranty

Smart
Yarn

Phthalate
free

Fabrication guide & cleaning instructions available upon request

* This material will behave similar to a velvet; fabricate from only one direction off the role. Please review the fabrication instruction manual and video for this product prior to use.

** Multiple factors effect coated fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be a reliable indicator of increased coated fabric lifespan.

† Industrial capacity operational in 2022

Quoted technical characteristics are average values with a +/- 5% tolerance. Our products are subject to improvements resulting from technical developments and we reserve the right to modify their characteristics at any time. The purchaser of our products is responsible for checking the above data.