SUNBRELLA Fabrics

This carefully curated collection of recommended Sunbrella fabrics is available on all Pavilion cushions and pillows.





SUNBRELLA FABRICS, CONTINUED

Spectrum Cilantro

Canvas Ginkgo





Canvas Forest Green

GRADING CHART

PATTERN NAME	GRADE	PATTERN NAME	GRADE
ACTION	D	DUPIONE PAPAYA	С
BLEND	С	ECHO	С
BLISS	Α	HERITAGE	D
CANVAS	Α	LINEN	Α
CAST	Α	NURTURE	Ε
DUPIONE CELESTE	В	SAILCLOTH	D
DUPIONE DEEP SEA	В	SPECTRUM	Α

SUNBRELLA UPHOLSTERY

As the leading performance fabric with the most comprehensive warranty in the industry, Sunbrella® fabrics offer best-in-class comfort, color retention, cleanability, and strength that lasts.

Weather Resistant

Sunbrella fabrics resist the damaging effects of sun, rain, snow, and humidity.

Stain Resistant

Engineered to resist stains and repel water, Sunbrella fabrics are easy to clean with soap and water.

Comfortable

Sunbrella fabrics prove that you can enjoy the best of both worlds: durability and impeccable softness.

Fade, UV Resistant

All Sunbrella fabrics feature stabilized UV and color pigments to prevent fading, damage, or deterioration.

Mold, Mildew Resistant

Woven to stand up to the elements, all Sunbrella fabrics resist unwanted microbial growth that can occur on lingering residue if fabrics are not regularly cleaned. Should mold or mildew appear, simply spot clean with a bleach solution.

Long-Lasting

Sunbrella fabrics guarantee against abrasion, pilling, loss of color, and loss of strength and will stand up to years of normal wear, exposure, and cleaning.

5-Year Limited Warranty

We stand behind our fabrics with the most comprehensive warranty in the industry as the only performance fabric brand to guarantee against pilling and abrasion in addition to loss of color and strength.

Act Performance Standards

Certain Sunbrella® fabrics meet specific ACT Voluntary Performance Guidelines, as indicated with the following certifications:



Abrasion - Low Traffic

15,000 to 29,000 double rub Wyzenbeek abrasion rating.



Abrasion - High Traffic

30,000 to 100,000 double rub Wyzenbeek abrasion rating.



Flammability

Passes California Technical Bulletin 117-2013 Section 1.



Wet, Dry Crocking

AATCC 8 with Grade 3 minimum for Wet Crocking and Grade 4 minimum for Dry Crocking.



Colorfastness to Light

AATCC 16 Option 1 or 3 test approval and meets Grade 4 minimum at 40 hours



Physical Properties

Pilling – Meets ASTM D3511 (Brush Pill), Class 3 minimum; Breaking Strength – Meets ASTM D5034 (Grab Test), 50 lbs. minimum in warp and weft.

Seam Slippage – Meets ASTM D4034, 25 lbs. minimum in warp and weft.

